

TECHNICAL DATA SHEET



J30100 | S-RACE® tacky | 100 g/m²
Microporous Coated Sublimation Paper

PRODUCT SPECIFICATION*

Grammage	100 g/m ² ± 6 g/m ²
Thickness	127 µm ± 6 µm 5.0 mil ± 0.25 mil

KEY APPLICATIONS

- › Transfer on all kinds of polyester materials
- › Especially designed for elastic textiles, no movement between paper and fabric during transfer (eliminates possible ghosting effect)
- › For medium to high ink coverage

BENEFITS & PROPERTIES

- › Optimal tack between paper and fabric during sublimation transfer (no ghosting)
- › Extremely fast drying
- › Excellent line sharpness
- › Superb and quick transfer properties
- › Outstanding lay-flat performance
- › Exceptional quality consistency

S-RACE® tacky J30100

Width (cm)	Roll length (m)	Core	Roll diameter (mm)
111.8	92 135	3 Inch	150 170
132.0	135	3 Inch	170
162.0	135 310 600	3 Inch	170 250 300
182.9	135 310 600	3 Inch	170 250 300

Further widths, lengths and core sizes are available on request, also jumbo rolls.

i Please note: the outer side of the roll (yellowish side) is the printing side. Don't print on the brighter side!

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH).
Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 08/2017