

DTF-A602/603/604

DIRECT TO FILM PRINTER



Self-development



long life




High precision




low cost

TECHNICAL PARAMETER

Model	DTF-A602		DTF-A603	DTF-A604
Printhead	Epson I3200-A1/Epson I1600-A1			
Printhead Quantity	2		3	4
Printing Color	4C+W		4C+Fo+Fm+Fy+Fg+W	4C+W
Printing Speed	I3200-A1	High speed mode	720*1800DPI 6PASS 10m²/h 720*2400DPI 8PASS 8m²/h	720*1200DPI 4PASS 23m²/h 720*1800DPI 6PASS 15m²/h 720*2400DPI 8PASS 11m²/h
		High precision mode	720*1800DPI 6PASS 5m²/h 720*2400DPI 8PASS 4m²/h	720*1200DPI 4PASS 18m²/h 720*1800DPI 6PASS 12m²/h 720*2400DPI 8PASS 9m²/h
	I1600-A1	720*900DPI 6PASS 4m²/h 720*1200DPI 8PASS 3m²/h 720*1800DPI 12PASS 2m²/h		720*900DPI 6PASS 13m²/h 720*1200DPI 8PASS 9m²/h 720*1800DPI 8PASS 6m²/h
				720*900DPI 6PASS 10m²/h 720*1200DPI 8PASS 7m²/h 720*1800DPI 8PASS 5m²/h
Printing Size	600mm			
Heating Method	Front and back independent heating			
Ink System	Auto ink supply,white ink circulating and stirring			
Power Supply	110V/220V 50~60HZ 350W/3500W			
Work Environment	Temperature:20℃~30℃ Humidity:35%~65%			
Machine size/weight	Printer: 1801*719*1597mm 200kg Powder Shaker: 970*988*1026mm 99kg			
Packaging Size/weight	Printer: 1890*740*850mm 213kg Powder Shaker: 920*730*1170mm 126kg			




Saves freight and space



Anti-collision system



3-stage heating zones



Powder auto-recycling device