

DTF-A30

DIRECT TO FILM PRINTER



Self-development



long life




High precision




low cost

TECHNICAL PARAMETER


Model	DTF-A30	
Printhead	2*Epson F1080	
Printing Color	4C+W or 6C+W(Lc/Lm/Fo/Fg as option)	
Printing Speed	High speed mode	720*360DPI 4PASS 5m²/h 720*540DPI 6PASS 4m²/h 720*720DPI 8PASS 3m²/h
	High precision mode	720*360DPI 4PASS 3.5m²/h 720*540DPI 6PASS 2.3m²/h 720*720DPI 8PASS 2.2m²/h
Printing Size	300mm	
RIP Software	RIIN/Flexiprint/CADlink/Maintop	
Media Transfer	Auto feeding and take-up system	
Heating Method	Front and back independent heating	
Ink System	Auto ink supply,white ink circulating and stirring	
Power Supply	110V/220V 50~60HZ 200W/1500W	
Work Environment	Temperature:20°C~30°C Humidity:35%~65%	
Machine Size/Weight	Printer: 940*762*978.3mm 80kg Powder Shaker: 640*932*577mm 45kg	
Packaging Size/Weight	Printer: 107*640*650mm 96kg Powder Shaker: 800*600*720mm 56kg	




High precision guide rail



Paper-lack sensor



Ink shortage alarming



White stir & circulate